

HEIGHT ADJUSTABLE FRONT SEATBELTS	STD	STD	STD	STD	STD	STD	STD
FRONT SEATBELT PRETENSIONERS WITH FORCE LIMITERS	STD	STD	STD	STD	STD	STD	STD
HEIGHT ADJUSTABLE FRONT HEAD RESTRAINTS	STD	STD	STD	STD	STD	STD	STD
RISE BODY CONSTRUCTION	STD	STD	STD	STD	STD	STD	STD
REAR CENTRE HIGH MOUNT STOP LAMP	STD	STD	STD	STD	STD	STD	STD
LED DAYTIME RUNNING LAMPS	STD	STD	STD	STD	STD	STD	STD
TIRE PRESSURE MONITORING SYSTEM (TPMS)	STD	STD	STD	STD	STD	STD	STD
HILL START ASSIST	STD	STD	STD	STD	STD	STD	STD
LANE DEPARTURE WARNING (LDW)	-	-	STD	-	-	-	STD
FORWARD COLLISION MITIGATION (FCM)	-	-	STD	-	-	-	STD
ADAPTIVE CRUISE CONTROL (ACC)	-	-	STD	-	-	-	STD
BLIND SPOT WARNING (BSW)	-	STD	STD	-	STD	STD	STD
REAR CROSS TRAFFIC ALERT (RCTA)	-	STD	STD	-	STD	STD	STD
WHEEL LOCKS	ACC	ACC	ACC	ACC	ACC	ACC	ACC

PERFORMANCE

2.4 L SOHC MIVEC 4 CYLINDER ENGINE	STD	STD	STD	-	-	-	-
3.0 L SOHC MIVEC 6 CYLINDER ENGINE	-	-	-	STD	STD	STD	STD
CONTINUOUSLY VARIABLE TRANSMISSION (CVT)	STD	STD	STD	-	-	-	-

6-SPEED AUTOMATIC TRANSMISSION WITH IDLE NEUTRAL LOGIC	-	-	-	STD	STD	STD	STD
PADDLE SHIFTERS	-	-	-	STD	STD	STD	STD
SUPER ALL-WHEEL CONTROL (S-AWC) WITH DRIVE MODE SELECTOR (ECO/NORMAL/SNOW/GRAVEL)	STD	STD	STD	STD	STD	STD	STD
FRONT MACPHERSON STRUT AND REAR MULTI-LINK SUSPENSION	STD	STD	STD	STD	STD	STD	STD
FRONT AND REAR STABILIZER BAR	STD	STD	STD	STD	STD	STD	STD
VENTILATED FRONT DISC AND SOLID REAR DISC BRAKES	STD	STD	STD	STD	STD	STD	STD
VARIABLE ASSISTED POWER RACK AND PINION STEERING	STD	STD	STD	STD	STD	STD	STD
ELECTRIC PARKING BRAKE	STD	STD	STD	STD	STD	STD	STD
EXTERIOR							
16" ALLOY WHEELS	STD	-	-	STD	-	-	-
18" ALLOY WHEELS	-	STD	STD	-	STD	-	STD
18" BLACK-PAINTED ALLOY WHEELS	-	-	-	-	-	STD	-
P215/70 R16 ALL-SEASON TIRES	STD	-	-	STD	-	-	-
P225/55 R18 ALL-SEASON TIRES	-	STD	STD	-	STD	STD	STD
TIRE REPAIR KIT	STD	STD	STD	STD	STD	STD	STD
FRONT AND REAR SILVER SKID PLATE STYLING	STD	STD	STD	STD	STD	-	STD
FRONT AND REAR BLACK SKID PLATE STYLING	-	-	-	-	-	STD	-

SKI AND SNOWBOARD CARRIER	ACC	ACC	ACC	ACC	ACC	ACC	ACC
UPRIGHT BIKE CARRIER	ACC	ACC	ACC	ACC	ACC	ACC	ACC
PARKING SENSOR ECU KIT	ACC	ACC	ACC	ACC	ACC	ACC	ACC
PULSE MEDIUM ROOF BOX 614	ACC	ACC	ACC	ACC	ACC	ACC	ACC
FORCE XT ROOF BOX LARGE	ACC	ACC	ACC	ACC	ACC	ACC	ACC
FORCE XT ROOF BOX EXTRA LARGE	ACC	ACC	ACC	ACC	ACC	ACC	ACC
EVO WINGBAR 53"	ACC	ACC	ACC	ACC	ACC	ACC	ACC
THULE COMPASS KAYAK AND SUP CARRIER	ACC	ACC	ACC	ACC	ACC	ACC	ACC
PRORIDE XT BIKE CARRIER ROOF MOUNT	ACC	ACC	ACC	ACC	ACC	ACC	ACC
CAMBER HITCH MOUNTED 4 BIKE CARRIER	ACC	ACC	ACC	ACC	ACC	ACC	ACC
CAMBER HITCH MOUNTED 2 BIKE CARRIER	ACC	ACC	ACC	ACC	ACC	ACC	ACC
THULE SNOWPAK L SKI SNOWBOARD CARRIER	ACC	ACC	ACC	ACC	ACC	ACC	ACC

INTERIOR

HEATED FRONT SEATS	STD	STD	STD	STD	STD	STD	STD
6-WAY ADJUSTABLE DRIVER'S SEAT (SLIDING, RECLINING AND HEIGHT ADJUSTABLE)	STD	-	-	STD	-	-	-
6-WAY POWER DRIVER'S SEAT (SLIDING, RECLINING AND HEIGHT ADJUSTABLE)	-	STD	STD	-	STD	STD	STD
4-WAY ADJUSTABLE FRONT PASSENGER SEAT	STD	-	-	STD	-	-	-
4-WAY POWER FRONT PASSENGER SEAT	-	STD	STD	-	STD	STD	STD

MICRON AIR FILTRATION	STD	STD	STD	STD	STD	STD	STD
REAR HEATER FLOOR DUCTS	STD	STD	STD	STD	STD	STD	STD
REAR HEATER DUCTS (BACK OF FRONT CENTRE CONSOLE)	STD	STD	STD	STD	STD	STD	STD
BLUETOOTH® HANDS-FREE CELLULAR PHONE INTERFACE	STD	STD	STD	STD	STD	STD	STD
POWER DOOR LOCKS WITH REMOTE KEYLESS ENTRY AND PANIC ALARM	STD	-	-	-	-	-	-
FAST-KEY KEYLESS ENTRY WITH PUSH-BUTTON START AND PANIC ALARM	-	STD	STD	STD	STD	STD	STD
POWER WINDOWS WITH AUTO-UP AND DOWN FUNCTION (ALL FOR DRIVER)	STD	STD	STD	STD	STD	STD	STD
ILLUMINATED WINDOW SWITCHES	STD	STD	STD	STD	STD	STD	STD
CRUISE CONTROL WITH STEERING WHEEL-MOUNTED CONTROLS	STD	STD	STD	STD	STD	STD	STD
ADAPTIVE CRUISE CONTROL (ACC)	-	-	STD	-	-	-	STD
8" SMARTPHONE LINK DISPLAY AUDIO WITH ANDROID AUTO™ AND APPLE CARPLAY	STD	STD	-	STD	STD	STD	-
8" MITSUBISHI POWER SOUND SMARTPHONE DISPLAY AUDIO WITH ANDROID AUTO™ AND APPLE CARPLAY	-	-	STD	-	-	-	STD
6 SPEAKERS	STD	STD	-	STD	STD	STD	-
8 SPEAKERS	-	-	STD	-	-	-	STD
SIRIUSXM® SATELLITE RADIO WITH 3 MONTHS COMPLIMENTARY SERVICE	STD	STD	STD	STD	STD	STD	STD
REARVIEW CAMERA	STD	STD	-	STD	STD	STD	-

EXTERIOR COLOURS

QUARTZ BROWN	STD	STD	STD	STD	STD	-	STD
COSMIC BLUE	STD	STD	STD	STD	STD	-	STD
TITANIUM GREY	STD	STD	STD	STD	STD	STD	STD
STERLING SILVER	STD	STD	STD	STD	STD	-	STD
RED DIAMOND	OPT	OPT	OPT	OPT	OPT	OPT	OPT
PEARL WHITE	OPT	OPT	OPT	OPT	OPT	OPT	OPT
LABRADOR BLACK	OPT	OPT	OPT	OPT	OPT	OPT	OPT

INTERIOR COLOURS

BLACK FABRIC	STD	-	-	STD	-	-	-
BLACK ARTIFICIAL SUEDE	-	STD	-	-	STD	STD	-
BLACK LEATHER	-	-	STD	-	-	-	STD

ENGINE

DRIVETRAIN	S-AWC	S-AWC	S-AWC	S-AWC	S-AWC	S-AWC	S-AWC
ENGINE TYPE	2.4 L MIVEC I-4	2.4 L MIVEC I-4	2.4 L MIVEC I-4	3.0 L MIVEC V6	3.0 L MIVEC V6	3.0 L MIVEC V6	3.0 L MIVEC V6
ENGINE CODE	4J12	4J12	4J12	6B31	6B31	6B31	6B31
VALVE TRAIN	SOHC 16-valve, Mitsubishi Innovative Valve-timing Electronic Control system (MIVEC)	SOHC 16-valve, Mitsubishi Innovative Valve-timing Electronic Control system (MIVEC)	SOHC 16-valve, Mitsubishi Innovative Valve-timing Electronic Control system (MIVEC)	SOHC 24-valve, Mitsubishi Innovative Valve-timing Electronic Control system (MIVEC)	SOHC 24-valve, Mitsubishi Innovative Valve-timing Electronic Control system (MIVEC)	SOHC 24-valve, Mitsubishi Innovative Valve-timing Electronic Control system (MIVEC)	SOHC 24-valve, Mitsubishi Innovative Valve-timing Electronic Control system (MIVEC)
DISPLACEMENT (CC)	2,360 cc	2,360 cc	2,360 cc	2,998 cc	2,998 cc	2,998 cc	2,998 cc

BORE X STROKE (MM)	88.0 x 97.0 mm	88.0 x 97.0 mm	88.0 x 97.0 mm	87.6 x 82.9 mm	87.6 x 82.9 mm	87.6 x 82.9 mm	87.6 x 82.9 mm
COMPRESSION RATIO	10.5:1	10.5:1	10.5:1	10.5:1	10.5:1	10.5:1	10.5:1
HORSEPOWER @ RPM	166 hp @ 6,000 rpm	166 hp @ 6000 rpm	166 hp @ 6000 rpm	224 hp @ 6,250 rpm	224 hp @ 6,250 rpm	224 hp @ 6,250 rpm	224 hp @ 6,250 rpm
TORQUE @ RPM (LB.-FT.)	162 lb.-ft. @ 4,200 rpm	162 lb.-ft. @ 4,200 rpm	162 lb.-ft. @ 4,200 rpm	215 lb.-ft. @ 3,750 rpm	215 lb.-ft. @ 3,750 rpm	215 lb.-ft. @ 3,750 rpm	215 lb.-ft. @ 3,750 rpm
ENGINE BLOCK	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
CYLINDER HEADS	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
REDLINE RPM	6,500 rpm	6,500 rpm	6,500 rpm	6,500 rpm	6,500 rpm	6,500 rpm	6,500 rpm
FUEL SYSTEM	MPI	MPI	MPI	MPI	MPI	MPI	MPI
EMISSIONS	TIER 3-BIN 70	TIER 3-BIN 70	TIER 3-BIN 70	TIER 3-BIN 70	TIER 3-BIN 70	TIER 3-BIN 70	TIER 3-BIN 70
RECOMMENDED FUEL	Regular Unleaded	Regular Unleaded	Regular Unleaded	Premium Unleaded	Premium Unleaded	Premium Unleaded	Premium Unleaded
ENGINE OIL TYPE	0W-20	0W-20	0W-20	0W-20	0W-20	0W-20	0W-20

TRANSMISSION							
TYPE	CVT	CVT	CVT	6AT	6AT	6AT	6AT
CONTINUOUSLY VARIABLE TRANSMISSION (CVT)	STD	STD	STD	-	-	-	-
6-SPEED AUTOMATIC TRANSMISSION WITH IDLE NEUTRAL LOGIC	-	-	-	STD	STD	STD	STD
PADDLE-SHIFTERS	-	-	-	STD	STD	STD	STD
CVT AUTOMATIC RATIOS	2.631 - 0.378	2.631 - 0.378	2.631 - 0.378	-	-	-	-
1ST	-	-	-	4.199	4.199	4.199	4.199
2ND	-	-	-	2.405	2.405	2.405	2.405
3RD	-	-	-	1.583	1.583	1.583	1.583

4TH	-	-	-	1.161	1.161	1.161	1.161
5TH	-	-	-	0.855	0.855	0.855	0.855
6TH	-	-	-	0.685	0.685	0.685	0.685
REVERSE	1.960	1.960	1.960	3.457	3.457	3.457	3.457
FINAL DRIVE	6.026	6.026	6.026	3.360	3.360	3.360	3.360

STEERING

TYPE	Electric Power Steering (EPS)	Electric Power Steering (EPS)	Electric Power Steering (EPS)	Electric Power Steering (EPS)	Electric Power Steering (EPS)	Electric Power Steering (EPS)	Electric Power Steering (EPS)
RATIO	14.7	14.7	14.7	14.7	14.7	14.7	14.7
TURNING CIRCLE (M/FT.)	10.6 m / 34.8 ft.	10.6 m / 34.8 ft.	10.6 m / 34.8 ft.	10.6 m / 34.8 ft.	10.6 m / 34.8 ft.	10.6 m / 34.8 ft.	10.6 m / 34.8 ft.
TURNS - LOCK TO LOCK	2.9	2.9	2.9	2.9	2.9	2.9	2.9

BRAKES

FRONT BRAKE TYPE	Ventilated disc	Ventilated disc	Ventilated disc	Ventilated disc	Ventilated disc	Ventilated disc	Ventilated disc
FRONT BRAKE DIAMETER (MM/IN.)	294 mm / 11.6 in.	294 mm / 11.6 in.	294 mm / 11.6 in.	294 mm / 11.6 in.	294 mm / 11.6 in.	294 mm / 11.6 in.	294 mm / 11.6 in.
REAR BRAKE TYPE	Solid disc	Solid disc	Solid disc	Solid disc	Solid disc	Solid disc	Solid disc
REAR BRAKE DIAMETER (MM/IN.)	302 mm / 11.9 in.	302 mm / 11.9 in.	302 mm / 11.9 in.	302 mm / 11.9 in.	302 mm / 11.9 in.	302 mm / 11.9 in.	302 mm / 11.9 in.
ANTI-LOCK BRAKING SYSTEM	4 sensor, 4 channel with Electronic Brake Distribution	4 sensor, 4 channel with Electronic Brake Distribution	4 sensor, 4 channel with Electronic Brake Distribution	4 sensor, 4 channel with Electronic Brake Distribution	4 sensor, 4 channel with Electronic Brake Distribution	4 sensor, 4 channel with Electronic Brake Distribution	4 sensor, 4 channel with Electronic Brake Distribution

SUSPENSION

FRONT	MacPherson Strut with Stabilizer Bar	MacPherson Strut with Stabilizer Bar	MacPherson Strut with Stabilizer Bar	MacPherson Strut with Stabilizer Bar	MacPherson Strut with Stabilizer Bar	MacPherson Strut with Stabilizer Bar	MacPherson Strut with Stabilizer Bar
REAR	Multi-link with Stabilizer Bar	Multi-link with Stabilizer Bar	Multi-link with Stabilizer Bar	Multi-link with Stabilizer Bar	Multi-link with Stabilizer Bar	Multi-link with Stabilizer Bar	Multi-link with Stabilizer Bar

EXTERIOR DIMENSIONS

WHEELBASE (MM/IN.)	2,670 mm / 105.1 in.	2,670 mm / 105.1 in.	2,670 mm / 105.1 in.	2,670 mm / 105.1 in.	2,670 mm / 105.1 in.	2,670 mm / 105.1 in.	2,670 mm / 105.1 in.
LENGTH (MM/IN.)	4,695 mm / 184.8 in.	4,695 mm / 184.8 in.	4,695 mm / 184.8 in.	4,695 mm / 184.8 in.	4,695 mm / 184.8 in.	4,695 mm / 184.8 in.	4,695 mm / 184.8 in.
WIDTH (MM/IN.)	1,810 mm / 71.3 in.	1,810 mm / 71.3 in.	1,810 mm / 71.3 in.	1,810 mm / 71.3 in.	1,810 mm / 71.3 in.	1,810 mm / 71.3 in.	1,810 mm / 71.3 in.
HEIGHT (MM/IN.)	1,710 mm / 67.3 in.	1,710 mm / 67.3 in.	1,710 mm / 67.3 in.	1,710 mm / 67.3 in.	1,710 mm / 67.3 in.	1,710 mm / 67.3 in.	1,710 mm / 67.3 in.
TRACK, FRONT (MM/IN.)	1,540 mm / 60.6 in.	1,540 mm / 60.6 in.	1,540 mm / 60.6 in.	1,540 mm / 60.6 in.	1,540 mm / 60.6 in.	1,540 mm / 60.6 in.	1,540 mm / 60.6 in.
TRACK, REAR (MM/IN.)	1,540 mm / 60.6 in.	1,540 mm / 60.6 in.	1,540 mm / 60.6 in.	1,540 mm / 60.6 in.	1,540 mm / 60.6 in.	1,540 mm / 60.6 in.	1,540 mm / 60.6 in.
MINIMUM GROUND CLEARANCE (MM/IN.)	215 mm / 8.5 in.	215 mm / 8.5 in.	215 mm / 8.5 in.	215 mm / 8.5 in.	215 mm / 8.5 in.	215 mm / 8.5 in.	215 mm / 8.5 in.

INTERIOR DIMENSIONS

PASSENGER SEATING CAPACITY	7	7	7	7	7	7	7
INTERIOR PASSENGER VOLUME WITH SUNROOF (L/CU. FT.)	-	3,562 L / 125.8 cu. ft.	3,562 L / 125.8 cu. ft.	-	3,562 L / 125.8 cu. ft.	3,562 L / 125.8 cu. ft.	3,562 L / 125.8 cu. ft.
INTERIOR PASSENGER VOLUME WITHOUT SUNROOF (L/CU. FT.)	3,630 L / 128.2 cu. ft.	-	-	3,630 L / 128.2 cu. ft.	-	-	-
CARGO AREA (BEHIND FRONT SEAT) WITH SUNROOF (L/CU. FT.)	-	1,727 L / 61.0 cu. ft.	1,727 L / 61.0 cu. ft.	-	1,727 L / 61.0 cu. ft.	1,727 L / 61.0 cu. ft.	1,727 L / 61.0 cu. ft.

SCUFF PLATES, 4 PC, WITH ILLUMINATION	ACC	ACC	ACC	ACC	ACC	ACC	ACC
PARKING SENSOR FRONT KIT	ACC	ACC	ACC	ACC	ACC	ACC	ACC
TRAILER TOW WIRE HARNESS, 4-FLAT CONNECTOR	ACC	ACC	ACC	ACC	ACC	ACC	ACC
PARKING SENSOR ECU KIT	ACC	ACC	ACC	ACC	ACC	ACC	ACC
PARK SENSOR REAR KIT	ACC	ACC	ACC	ACC	ACC	ACC	ACC

FUEL CAPACITY

FUEL TANK CAPACITY (L/IMP. GAL.)	60 L / 13.2 gal.	60 L / 13.2 gal.	60 L / 13.2 gal.	60 L / 13.2 gal.	60 L / 13.2 gal.	60 L / 13.2 gal.	60 L / 13.2 gal.
---	------------------	------------------	------------------	------------------	------------------	------------------	------------------

ESTIMATED FUEL CONSUMPTION

DRIVETRAIN	CVT S-AWC	CVT S-AWC	CVT S-AWC	6AT S-AWC	6AT S-AWC	6AT S-AWC	6AT S-AWC
CITY (L/100KM)	9.9	9.9	9.9	12	12	12	12
HIGHWAY (L/100KM)	8.1	8.1	8.1	8.8	8.8	8.8	8.8
COMBINED (L/100KM)	9.1	9.1	9.1	10.6	10.6	10.6	10.6

WHEELS & TIRES

WHEEL TYPE	16x6.5J Aluminum	18x7J Aluminum	18x7J Aluminum	16x6.5J Aluminum	18x7J Aluminum	18x7J Aluminum	18x7J Aluminum
WHEEL SIZE	16 inch	18 inch	18 inch	16 inch	18 inch	18 inch	18 inch
TIRE SIZE	P215/70R16	P225/55R18	P225/55R18	P215/70R16	P225/55R18	P225/55R18	P225/55R18
TIRE REPAIR KIT	STD	STD	STD	STD	STD	STD	STD

WARRANTIES

